

COAX 15

Two-way loudspeaker system



The COAX 15 is a compact, 15" LF driver and 1" exit HF driver, 2-way, highly weather-resistant full range loudspeaker with high SPL, the body is made of engineering plastic injection molding. The system conforms to IP65 international standard.

Features

- Highly weather-resistant IP65 rating
- Engineering plastic injection molding
- High SPL
- Coaxial components design
- Good used for speech, music in multi-purpose applications, sports facilities, stadiums, water parks, outdoor background music, swimming pools and a wide variety of other indoor or outdoor venue types.



Overall dimensions



Technical specifications

FREQUENCY RESPONSE (-3dB)	60 Hz-15kHz
DRIVERS	1x15"(385mm)/3" voice coil LF 1x1"(25mm)/1.7" voice coil HF
POWER	800W RMS, 1600W peak
SENSITIVITY	103 dB 1 watt/1 metre
MAXIMUM SPL	129 dB continuous, 136 dB peak
IMPEDANCE	8 ohms nominal
DISPERSION(-6 dB)	90°x60° - 90°x90° nominal
CROSSOVER	1.2 kHz passive
INPUT CONNECTORS	covered barrier strip terminals
DIMENSIONS	(W)498mm×(H)501mm×(D)596mm
WEIGHT	25 kg

