Voice Alarm Remote Microphone EVAC-500RM

Features:

- ✓ Digital voice evacuation system remote paging microphone.
- ✓ Each microphone of 12 zone capacity.
- ✓ System support 32 remote microphones of loop connection.
- ✓ System indicators of AC, DC, fault, Mic status and test.
- √ 6 inputs & mic/line selection buttons.
- √ 6 zone selection buttons with three-colored indicators
- ✓ Reset/Cancel, All Call & Call buttons.
- ✓ Two RJ45 ports for input and link output.
- ✓ CAT5 or CAT6 cable communication up to 600 meters.
- ✓ AC 230V and DC24V battery inputs.
- ✓ Built-in monitor speaker.



Specifications:

Model	EVAC-500RM
Description	Voice Alarm Remote Microphone
Power Consumption	3W
Zone Capacity	12 Zones
System Capacity	32 Remote microphones
Line Inputs	350mV, 10kΩ
Mic Input	5mV, 600Ω
Frequency Response	80Hz~16kHz
THD	<1% at RMS,1KHz
S/N Ratio	>70dB
Operating Temp	-20℃ to +70℃
Power Supply	DC24V, ±20%
Humidity	<95% no condensation
Dimension	256(W)×149(H)×52(D) mm
Weight	1.5kg

Rear Panel:



