

DS EN 40

EN54-24 Outdoor Column Speaker

FEATURE

- Commercial public address (PA) system music & paging horn speaker with transformer
- Ideal for outdoor music and speech use in factory, school, office, hotel and airport
- Compliant with the EN54-24 standards
- Fireproof speaker tail, 95°C fire-resistant cable and thermal fuse
- 2×3" + 2.5" two way fire resistant speaker system
- Rated power output 40W-20W-10W & 8 Ohm
- Waterproof level of IP66
- Line input 100V by fire-resistant cable tail with waterproof gland
- Aluminum alloy enclosure in white
- Quick installation by supplied stainless mounting bracket



Description	: Outdoor Column Speaker
Max Power Output	: 60W
Rated Power Output	: 40W-20W-10W & 8 ohm
Speaker	: 2×3" + 2.5" two way fire resistant speaker system
Line Input	: 100V
Frequency Response	: 150-20KHz
SPL(@1W/m)	: 115/99dB(SPL)
IP Rate	: IP66
Coverage Angle	: 220° x 138° (horizontal), 55° x 25° (vertical)
Temperature	: -25°C + 55°C
Connector	: By fire-resistant cable tail with waterproof gland
Dimension	: 395×107×105mm
Material	: Aluminum alloy enclosure and stainless metal bracket in white
Mounting Way	: Quick installation by supplied stainless mounting bracket
Net Weight	: 3kg

